




INNOVATING FOR A BETTER WORLD



Technical Data Sheet of ela3000 anolyte (HClO) generator

External view of ela3000




On site installations of ela3000




Specifications/Models	ela3000
Output capacity of anolyte	Total output ~300 LPH of ANK - Neutral Anolyte with ~500 ppm of FAC
pH of HClO	Regulation of pH in the range pH ~2.5-8.5
NaCl consumption	5-6 g per 1 L of 500 ppm HClO Lower salt consumption on request
Weight of the generator	~70 kg
Crated weight	~80 kg


Dimensions of ela3000





Crated dimensions of ela3000



Mounting dimensions of ela3000




Power supply	400 VAC / 50-60 Hz. Alternatives are possible
Power consumption	~ 4.1 kW/h
Automated flushing	+
Acid pump	+
Brine pump	+
Input valve	+
Flow and pressure switchers/ controllers	+
Temperature switchers on the cells	+
Durability	Able to stand up to adverse conditions such as dust and high humidity
Life expectancy of electrodes and membrane	~ 10 years
Type of cell	  R/RT-300
Fittings	LLDPE tubing + Kynar fittings
PLC Unitronics	 Vision 130 Alternatives are possible

Accessories


- Main water tubing ~ 2 m
- Anolyte tubing ~ 2 m
- Catholyte tubing ~ 2 m
- Brine tubing ~ 2 m
- Acid tubing ~ 2 m
- Salt filter – 1 pcs
- Mains water fitting – 1 pcs
- Wall mounting lugs – 1 set
- Level switch for anolyte tank – 1 set

Options

- Produced in 2 boxes: 820x610 mm or 1020x810 mm



In two 820x610 mm boxes



In two 1020x810 mm boxes

- Multicolor touchscreen PLC V570



- Remote control through Ethernet, Modbus TCP IP or GSM
- Inline pH sensor
- Inline ORP sensor
- Automatic pH correction
- Non-contact level sensor



Certified to
NSF/ANSI/CAN 61



Envirollyte Industries International Ltd.

Sarruse 16, Tallinn 13816, Estonia

Phone: +372 6626 630 | Fax: +372 6626 631 | E-mail: envirollyte@envirollyte.com | www.envirollyte.com